

DEUTZ-FAHR AGROLUX AGROLUX 60F

(2001-2010)

**ENGINE** Deutz F3L-914

Capacity: 10,5 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40*Change every 50 hours***DIFFERENTIAL FRONT**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Check every 10 hours, change every 1200 hours***HUB REDUCTIONS FRONT**

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Check every 10 hours, change every 1200 hours***TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING**

Capacity: 41 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 10 hours, change every 1200 hours*

DEUTZ-FAHR AGROLUX AGROLUX 60F

(2001-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.