## **DEUTZ-FAHR AGROTRON M AGROTRON M 610 ->20001** (2010-2013)



| <b>ENGINE</b> Deutz TCD 2012 L06 2V DCR Capacity: 13 liter, Filter capacity: 1 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40   | Agridiesel MSP 15W-40    | Agridiesel CRD+ 15W-40   |
| Check every 10 hours, change every 500   | hours/ 12 months         |                          |
| USE  |                          | CLIMATE                  |
| Initial service  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40   | Agridiesel MSP 15W-40    | Agridiesel CRD+ 15W-40   |
| Change every 100 hours   |                          |                          |
| USE  |                          | CLIMATE                  |
| Biodiesel B100   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40   | Agridiesel MSP 15W-40    | Agridiesel CRD+ 15W-40   |

| <b>DIFFERENTIAL FRONT</b> Capacity: 5,8 liter |                    |
|---|--------------------|
| USE   | CLIMATE            |
| Normal  | Moderate           |
| PRODUCT RECOMMENDATION 1                      |                    |
| Gearlube LS 80W-90                            |                    |
| Check every 250 hours, change eve             | 0 hours/ 12 months |

| HUB REDUCTIONS FRONT<br>Capacity: 0,8 liter (each hub)    |  |          |
|---|--|----------|
| USE   |  | CLIMATE  |
| Normal  |  | Moderate |
| PRODUCT RECOMMENDATION 1                                  |  |          |
| Gearlube LS 80W-90  |  |          |
| Check every 250 hours, change every 1000 hours/ 12 months |  |          |

Check every 10 hours, change every 250 hours/ 12 months

## **DEUTZ-FAHR AGROTRON M AGROTRON M 610 -> 20001** (2010-2013)



| HUB REDUCTIONS REAR<br>Capacity: 9 liter (each hub) |          |
|---|----------|
| USE   | CLIMATE  |
| Normal  | Moderate |
| PRODUCT RECOMMENDATION 1                            |          |
| Gearlube LS 80W-90                                  |          |
|   | ·        |

Check every 250 hours, change every 1000 hours/12 months

| POWER TAKE OFF FRONT<br>Capacity: 0,9 liter |                          |             |
|---|--------------------------|-------------|
| USE   |                          | CLIMATE     |
| Normal                                      |                          | Moderate    |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 |             |
| Agrifluid HT-Plus                           | Agrifluid HT             |             |
|   | <del></del>              | <del></del> |

Check every 250 hours, change every 500 hours

| TRANSMISSION Capacity: 78-80 liter                       |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                                 | PRODUCT RECOMMENDATION 2 |          |
| Agrifluid HT-Plus  | Agrifluid HT             |          |
| Check every 50 hours, change every 1000 hours/ 12 months |                          |          |

| HYDRAULIC BRAKE/CLUTCH SYSTEM |  |          |
|-------------------------------|--|----------|
| USE                           |  | CLIMATE  |
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| SP Matic 2032                 |  |          |

Check every 50 hours, change every 24 months

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

## **DEUTZ-FAHR AGROTRON M AGROTRON M 610 ->20001** (2010-2013)



| COOLING SYSTEM Capacity: 18 liter  |                       |          |
|------------------------------------|-----------------------|----------|
| USE                                |                       | CLIMATE  |
| Normal                             |                       | Moderate |
| PRODUCT RECOMMENDATION 1           |                       |          |
| Coolant SP 12 EVO                  |                       |          |
| Check every 10 hours, change every | 1000 hours/ 12 months |          |

Check every 10 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.