DEUTZ-FAHR AGROVECTOR AGROVECTOR 26.6 LP (2007-2010)



ENGINE Deutz BF4M-2012C Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agridiesel CRD+ 15W-40		
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agridiesel CRD+ 15W-40		
Change every 50 hours		
DIFFERENTIAL FRONT Capacity: 7,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
DIFFERENTIAL REAR Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
HUB REDUCTIONS REAR		
Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
	1	1

DEUTZ-FAHR AGROVECTOR AGROVECTOR 26.6 LP (2007-2010)



HYDROSTATIC DRIVE Capacity: 64 liter (Hydraulic tank), Capacity: 106 liter (Total)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Kroontrak MTH 10W-30				

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 50 hours	·	

COOLING SYSTEM Capacity: 15,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 1500 hours	'	-

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.