

DEUTZ-FAHR DX 6/7/8 DX 6.50 (1987-1991)

ENGINE Deutz BF6L-913
Capacity: 18 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Multifleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40*Change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 250 hours/ 12 months*

DIFFERENTIAL FRONT (4x4)
Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 500 hours, change every 1000 hours/ 12 months*

DEUTZ-FAHR DX 6/7/8 DX 6.50 (1987-1991)**HUB REDUCTIONS FRONT (4x4)**

Capacity: 0,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours/ 12 months***POWER TAKE OFF FRONT**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Multifleet SHPD 15W-40***Check every 500 hours, change every 2000 hours/ 24 months***TRANSAXLE MANUAL**

Capacity: 44 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Multifleet SHPD 15W-40***Check every 500 hours, change every 2000 hours/ 24 months***HYDRAULIC SYSTEM**

Capacity: 13 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Multifleet SCD 20W-20****PRODUCT RECOMMENDATION 2****HDX 20W-20***Check every 250 hours, change every 1000 hours/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 2000 hours/ 24 months*

DEUTZ-FAHR DX 6/7/8 DX 6.50 (1987-1991)**HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 2000 hours/ 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.