EICHER 2000 2090A 4WD (1990-1991)



ENGINE Perkins H-1000.4 WT Capacity: 9,2 liter	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Multifleet SCD 40	
Change every 150 hours	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 150 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	
Change every 150 hours	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	
Change every 150 hours	
DIFFERENTIAL FRONT Capacity: 6 liter	
USE	 CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

REDUCTION UNITS FRONT Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change every 1200 hours		

Check every 150 hours, change every 1200 hours

EICHER 2000 2090A 4WD (1990-1991)



TRANSAXLE/HYDRAULIC SYSTEM 40/40 Capacity: 52 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 150 hours, change every 1200 hours

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	
Check every 50 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours		'

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 1200 hours		'

COOLING SYSTEM Capacity: 13 liter, Capacity: 15 liter (+ heater)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Charles and A. harring above a com-	0.400 /	

Check every 10 hours, change every 2400 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.