

# FENDT FARMER 300 C FARMER 307 CI

## 117../8001 -> (2004-2008)



**ENGINE** Deutz BF4M-2012C  
Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

### DIFFERENTIAL FRONT LIMITED SLIP

Capacity: 6 liter (Flange 1660 mm), Capacity: 7,5 liter (Flange 1760 mm)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

### HUB REDUCTIONS FRONT

Capacity: 0,75 liter (Flange 1660 mm), Capacity: 0,9 liter (Flange 1760 mm)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

### HUB REDUCTIONS REAR

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 50 hours, change every 2000 hours/ 24 months*

### POWER TAKE OFF FRONT

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 50 hours, change every 2000 hours/ 24 months*

# FENDT FARMER 300 C FARMER 307 CI

## 117../8001 -> (2004-2008)



### TRANSAXLE MANUAL

Capacity: 35,5 liter, Capacity: 37,5 liter (+ front wheel drive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

Check every 10 hours, change every 2000 hours/ 24 months

### HYDRAULIC SYSTEM

Capacity: 41 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 20W-20</b>	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Kroontrak CVT 10W-40</b>	<b>Kroontrak MTH 10W-30</b>

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

### HYDRAULIC BRAKE SYSTEM

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

### PNEUMATIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Check every 50 hours

# FENDT FARMER 300 C FARMER 307 CI

## 117../8001 -> (2004-2008)

**COOLING SYSTEM**

Capacity: 13 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26**

*Check every 10 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*