

FENDT 800 VARIO COM3B 819 VARIO

STAGE IIIB / EPA 4I 832/./0101-> (2011-2016)



ENGINE Deutz TCD 6.1 L6
Capacity: 16,5 liter

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

Change every 50 hours

| USE | CLIMATE |
|--|----------|
| Normal, fuel sulfur level 500-5000 ppm | Moderate |

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT LIMITED SLIP

Capacity: 9-11 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HUB REDUCTIONS FRONT

Capacity: 1,8 liter (each hub)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

POWER TAKE OFF FRONT

Capacity: 3,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

Check every 500 hours, change every 2000 hours/ 24 months

FENDT 800 VARIO COM3B 819 VARIO

STAGE IIIB / EPA 4I 832/./0101-> (2011-2016)



TRANSAXLE Vario
Capacity: 145 liter (Dry fill), Capacity: 123 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

Check every 10 hours, change every 2000 hours/ 24 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

Check every 10 hours, change every 2000 hours/ 24 months

HYDRAULIC SYSTEM
Capacity: 102 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1
Perlus H 68

Check every 50 hours, change every 1000 hours/ 24 months

| USE | CLIMATE |
|--------------------------|---------------|
| Alternative (acceptable) | Mediterranean |

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Check every 50 hours, change every 1000 hours/ 24 months

| USE | CLIMATE |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| | |
|---|---|
| PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 | PRODUCT RECOMMENDATION 2 Kroontrak MTH 10W-30 |
|---|---|

Check every 50 hours, change every 1000 hours/ 24 months

| USE | CLIMATE |
|-------------------|----------|
| Biodegradable oil | Moderate |

| | |
|---|---|
| PRODUCT RECOMMENDATION 1 Perlus Biosynth 46 | PRODUCT RECOMMENDATION 2 Perlus Biosynth 32 |
|---|---|

Check every 10 hours, change every 1000 hours/ 12 months

FENDT 800 VARIO COM3B 819 VARIO

STAGE IIIB / EPA 4I 832/.. /0101-> (2011-2016)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,25 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3013 | | |

Change every 24 months

PNEUMATIC BRAKE SYSTEM

Capacity: 0,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

COOLING SYSTEM

Capacity: 35-45 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 24 months

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 42 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.