

# FENDT 900 VARIO COM3 FAVORIT 933

## VARIO 931/./0101 -> 931/./3500 (2006-2007)



**ENGINE** Deutz TCD 2013 L06 4V  
Capacity: 38 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Change every 50 hours*

### DIFFERENTIAL FRONT

Capacity: 16 liter (Dual brake system), Capacity: 34 liter (Single brake system)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Kroontrak CVT 10W-40</b>		

*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

### HUB REDUCTIONS FRONT

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	<b>Gearlube GL-5 85W-140</b>

*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

### HUB REDUCTIONS REAR

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 12 months/ 500 hours, change every 2000 hours/ 24 months*

# FENDT 900 VARIO COM3 FAVORIT 933

## VARIO 931../0101 -> 931../3500 (2006-2007)

**HUB REDUCTIONS REAR** Stummel

Capacity: 16 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

## PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140***Check every 10 hours, change every 2000 hours/ 24 months***POWER TAKE OFF FRONT**

Capacity: 3,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40***Check every 12 months/ 500 hours, change every 2000 hours/ 24 months***TRANSAXLE** Vario

Capacity: 67 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40***Check every 10 hours, change every 2000 hours/ 24 months*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40***Check every 10 hours, change every 2000 hours/ 24 months*

# FENDT 900 VARIO COM3 FAVORIT 933

## VARIO 931/./0101 -> 931/./3500 (2006-2007)

**HYDRAULIC SYSTEM**

Capacity: 109 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak CVT 10W-40</b>	<b>Kroontrak MTH 10W-30</b>	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

**HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

Check every 12 months/ 500 hours, change every 2000 hours/ 24 months

**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Check every 50 hours

**COOLING SYSTEM**

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.