

**FENDT P SERIES 8370 P (2009-2013)**

**ENGINE** Sisu  
Capacity: 27 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agridiesel MSP 15W-40**

PRODUCT RECOMMENDATION 2  
**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 3  
**Multifleet SHPD 15W-40**

*Check every 8 hours, change every 12 months/ 250 hours*

**CHAINS AND JOINTS**

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2  
**Unigear HS GL-3/GL-5 80W-90**

*Check every 10 hours*

**REDUCTION UNITS**

Capacity: 6 liter (each)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2  
**Unigear HS GL-3/GL-5 80W-90**

*Check every 100 hours, change every 500 hours*

**TRANSFERBOX**

Capacity: 1,5 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2  
**Unigear HS GL-3/GL-5 80W-90**

*Check every 100 hours, change every 500 hours*

**TRANSMISSION**

Capacity: 9,5 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2  
**Unigear HS GL-3/GL-5 80W-90**

*Check every 100 hours, change every 500 hours*

**FENDT P SERIES 8370 P (2009-2013)****HYDRAULIC SYSTEM**

Capacity: 34 liter (Reservoir), Capacity: 90 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 10 hours, change every 1000 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 10 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>

*Change every 50 hours***COOLING SYSTEM**

Capacity: 60 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 10 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.