

FENDT X SERIES 9470X AL (2011-2013)

ENGINE Citius 98 CTA SCR Stage IIb/Tier 4i
Capacity: 35 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP Ultra 10W-40
--	--	---

Check every 10 hours, change every 250 hours/ 12 months

CHAINS AND JOINTS

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 10 hours

REDUCTION UNITS

Capacity: 6 liter (each)

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 100 hours, change every 500 hours/ 24 months

ROTOR GEARBOX

Capacity: 1,5 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 100 hours, change every 250 hours/ 12 months

TRANSMISSION

Capacity: 9,5 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 100 hours, change every 500 hours/ 24 months

FENDT X SERIES 9470X AL (2011-2013)**HYDRAULIC SYSTEM**

Capacity: 90 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 68***Check every 10 hours, change every 1000 hours/ 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 100 hours***GREASE POINTS/NIPPLES KNIVES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**HT Q9 High Grade Grease****PRODUCT RECOMMENDATION 2****Labora Grease****PRODUCT RECOMMENDATION 3****Q5 MP Calcep Grease EP 2***Check every 10 hours***GREASE POINTS/NIPPLES OTHERS****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Change every 50 hours***COOLING SYSTEM**

Capacity: 65 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF***Check every 10 hours, change every 1000 hours/ 24 months*

FENDT X SERIES 9470X AL (2011-2013)**PUMP DRIVE GEARBOX**

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 100 hours, change every 250 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.