## **FIAT-TRATTORI 88 70-88, 70-88 DT** (1991-1993)



| <b>ENGINE</b> 8045.06<br>Capacity: 11,7 liter, Filter capacity: 1 liter |                          |                          |
|-------------------------------------------------------------------------|--------------------------|--------------------------|
| USE                                                                     |                          | CLIMATE                  |
| Normal                                                                  |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1                                                | PRODUCT RECOMMENDATION 2 |                          |
| Multifleet SCD 40                                                       | Multifleet SCD 30        |                          |
| Check every 10 hours, change every 200 h                                | nours                    | •                        |
| USE                                                                     |                          | CLIMATE                  |
| Normal                                                                  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                                                | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30                                                    | Multifleet SHPD 10W-40   | Multifleet SHPD 15W-40   |
| Check every 10 hours, change every 200 h                                | nours                    |                          |
| USE                                                                     |                          | CLIMATE                  |
| Normal                                                                  |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                                                |                          |                          |
| Multifleet SCD 20W-20                                                   |                          |                          |
| Check every 10 hours, change every 200 h                                | nours                    |                          |
| USE                                                                     |                          | CLIMATE                  |
| Normal                                                                  |                          | Arctic                   |
| PRODUCT RECOMMENDATION 1                                                |                          |                          |
| Multifleet SCD 10W                                                      |                          |                          |
| Check every 10 hours, change every 200 h                                | nours                    |                          |
|                                                                         |                          |                          |

| <b>DIFFERENTIAL FRONT</b> (4x4)<br>Capacity: 8,5 liter |                          |                          |
|--------------------------------------------------------|--------------------------|--------------------------|
| USE                                                    |                          | CLIMATE                  |
| Normal                                                 |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                               | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra                              | Kroontrak MTH 10W-30     | Agrifluid HT             |

Check every 400 hours, change every 1600 hours

| HUB REDUCTIONS FRONT (4x4)<br>Capacity: 1,2 liter |                          |                          |
|---------------------------------------------------|--------------------------|--------------------------|
| USE                                               |                          | CLIMATE                  |
| Normal                                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra                         | Kroontrak MTH 10W-30     | Agrifluid HT             |
|                                                   | / /                      |                          |

Check every 400 hours, change every 1600 hours

## **FIAT-TRATTORI 88 70-88, 70-88 DT** (1991-1993)



| TRANSAXLE/HYDRAULIC SYSTEM 20/12<br>Capacity: 54 liter |                          |                          |  |
|--------------------------------------------------------|--------------------------|--------------------------|--|
| USE                                                    |                          | CLIMATE                  |  |
| Normal                                                 |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1                               | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |
| Agrifluid Synth XHP Ultra                              | Kroontrak MTH 10W-30     | Agrifluid HT             |  |

Check every 400 hours, change every 1600 hours

| HYDRAULIC BRAKE SYSTEM<br>Capacity: 0,45 liter |          |
|------------------------------------------------|----------|
| USE                                            | CLIMATE  |
| Normal                                         | Moderate |
| PRODUCT RECOMMENDATION 1                       |          |
| Multifleet SCD 10W                             |          |

| POWER STEERING<br>Capacity: 2 liter |                          |                          |
|-------------------------------------|--------------------------|--------------------------|
| USE                                 |                          | CLIMATE                  |
| Normal                              |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra           | Kroontrak MTH 10W-30     | Agrifluid HT             |

Change every 800 hours

| GREASE POINTS/NIPPLES    |                          |          |
|--------------------------|--------------------------|----------|
| USE                      |                          | CLIMATE  |
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2  |          |
|                          |                          |          |

Check every 50 hours

| GREASE POINTS/NIPPLES KING PINS |                          |          |  |
|---------------------------------|--------------------------|----------|--|
| USE                             |                          | CLIMATE  |  |
| Normal                          |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2 |          |  |
| Q7 MP Calcep Grease WR 2        | Caliplex HD Grease EP 2  |          |  |
|                                 |                          |          |  |

Check every 400 hours

## **FIAT-TRATTORI 88 70-88, 70-88 DT** (1991-1993)



| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT |                          |          |  |
|--------------------------------------------|--------------------------|----------|--|
| USE                                        |                          | CLIMATE  |  |
| Normal                                     |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 |          |  |
| Q7 MP Calcep Grease WR 2                   | Caliplex HD Grease EP 2  |          |  |

Check every 400 hours

| COOLING SYSTEM<br>Capacity: 14 liter |                          |          |  |
|--------------------------------------|--------------------------|----------|--|
| USE                                  |                          | CLIMATE  |  |
| Normal                               |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 |          |  |
| Coolant -38 Organic NF               | Coolant -26              |          |  |
| Change every 1600 hours              | ·                        | ·        |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.