

FORD 30 4630 (1990-1996)

ENGINE BSD 333 H
Capacity: 6,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 10 hours, change every 300 hours*

DIFFERENTIAL FRONT (4x4)
Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus*Check every 50 hours, change every 1200 hours/ 12 months*

DIFFERENTIAL REAR/HYDRAULIC SYSTEM
Capacity: 32,5-45,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus*Check every 300 hours, change every 1200 hours/ 12 months*

FORD 30 4630 (1990-1996)**HUB REDUCTIONS FRONT (4x4)**

Capacity: 0,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 50 hours, change every 1200 hours/ 12 months***TRANSMISSION MANUAL ShuttleShift 16/8**

Capacity: 8,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 300 hours, change every 1200 hours/ 12 months***TRANSMISSION MANUAL ShuttleShift 8/8**

Capacity: 9,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 300 hours, change every 1200 hours/ 12 months***TRANSMISSION MANUAL CONSTANT MESH TRANSMISSION LESS DUAL POWER 8/2**

Capacity: 12 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 300 hours, change every 1200 hours/ 12 months***POWER STEERING**

Capacity: 2,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Check every 10 hours, change every 1200 hours/ 12 months*

FORD 30 4630 (1990-1996)**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MoS2 Grease EP 2	
<i>Check every 50 hours</i>		

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MoS2 Grease EP 2	
<i>Check every 50 hours, change every 600 hours</i>		

COOLING SYSTEM

Capacity: 11,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant -26	
<i>Check every 10 hours, change every 1200 hours/ 24 months</i>		

BELT PULLEY

Capacity: 1,13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus
<i>Check every 50 hours, change every 1200 hours/ 12 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.