

**FORD TF TF 44 (1983 AND AFTER)**

**ENGINE** Mercedes-Benz OM421A  
Capacity: 18,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 200 hours/ 12 months*

**DRUM SPEED REDUCER**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 10 hours, change every 200 hours*

**HUB REDUCTIONS FRONT**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 50 hours, change every 400 hours/ 12 months*

**HUB REDUCTIONS REAR (4x4)**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 50 hours, change every 400 hours/ 12 months*

**TRANSAXLE MANUAL 4/4**

Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 50 hours, change every 400 hours/ 12 months*

**FORD TF TF 44 (1983 AND AFTER)****HYDRAULIC SYSTEM**

Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>ATF-A</b>	<b>Perlus H 46</b>	<b>Perlus AF 46</b>

*Check every 10 hours, change every 400 hours/ 12 months***HYDRAULIC SYSTEM HYDROSTATIC DRIVE**

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>ATF-A</b>	<b>Perlus H 46</b>	<b>Perlus AF 46</b>

*Check every 10 hours, change every 400 hours/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 50 hours, change every 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>MoS2 Grease EP 2</b>	<b>Q5 MP Calcep Grease EP 2</b>

*Check every 10 hours***GREASE POINTS/NIPPLES AUGER DRIVE GEARBOX**

We are unable to give a standard recommendation for this component. Please contact our service department.

**GREASE POINTS/NIPPLES CLEANING SHOE DRIVE GEARBOXES**

We are unable to give a standard recommendation for this component. Please contact our service department.

**FORD TF TF 44 (1983 AND AFTER)****COOLING SYSTEM**

Capacity: 37 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10 hours, change every 1200 hours/ 24 months

**CHAINS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-1 80W-90</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*