

# HARDI SPRAYERS ALPHA 2000 DEUTZ BF4M 1012C (1997-2006)

**ENGINE** Deutz BF4M-1012C

Capacity: 10 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40***Check every 10 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40***Change every 50 hours***HYDROSTATIC DRIVE**

Capacity: 60 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

## PRODUCT RECOMMENDATION 2

**Perlus H 46***Check every 10 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

## PRODUCT RECOMMENDATION 2

**Perlus H 46***Check every 10 hours, change every 500 hours***GREASE POINTS/NIPPLES CHASSIS AND BOOM**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2***Change every 50 hours*

# HARDI SPRAYERS ALPHA 2000 DEUTZ BF4M 1012C (1997-2006)



## GREASE POINTS/NIPPLES DIAPHRAGM PUMP

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

## GREASE POINTS/NIPPLES OIL LUBRICATED

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 50 hours*

## COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 100 hours, change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.