

# HOLDER A-TRAC A-TRAC 5.62P (2006 AND AFTER)



**ENGINE** Deutz TCD 2011 L04i  
Capacity: 11,8 liter, Capacity: 12,55 liter (+ heater)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP 10W-40**

*Check every 10 hours, change every 500 hours/ 12 months*

## CREEP SPEED GEARBOX

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT**

*Check every 125 hours, change every 1500 hours*

## REVERSE GEAR UNIT

Capacity: 8,5 liter (Dry fill), Capacity: 7,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT**

*Check every 125 hours, change every 1500 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT**

*Change every 125 hours*

# HOLDER A-TRAC A-TRAC 5.62P (2006 AND AFTER)



## TRANSMISSION FRONT

Capacity: 18,5 liter (Dry fill), Capacity: 12,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Check every 125 hours, change every 1500 hours*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 125 hours*

## HYDRAULIC SYSTEM

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	<b>Perlus AF 46</b>

*Check every 125 hours, change every 1500 hours*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	<b>Perlus AF 46</b>

*Change every 500 hours*

## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 125 hours, change every 12 months*

# HOLDER A-TRAC A-TRAC 5.62P (2006 AND AFTER)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*