

# HOLDER A-TRAC A-TRAC 8.72C/H (2002-2007)



**ENGINE BT4L-1011F**  
Capacity: 8,75 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-------------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SHPD 10W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 450 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 15,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |

*Check every 150 hours, change every 1350 hours/ 12 months*

**TRANSAXLE MANUAL 12/4**  
Capacity: 10,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |

*Check every 150 hours, change every 1350 hours/ 12 months*

**HYDRAULIC SYSTEM**  
Capacity: 18 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |  |

*Check every 150 hours, change every 2700 hours/ 12 months*

**HYDROSTATIC DRIVE**  
Capacity: 13 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |  |

*Check every 150 hours, change every 2700 hours/ 12 months*

**HOLDER A-TRAC A-TRAC 8.72C/H (2002-2007)****HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,4 liter

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Check every 150 hours, change every 12 months***GREASE POINTS/NIPPLES**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Check every 20 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*