

HOLDER A SERIES A 550, A 550 S (1990-2001)



ENGINE Deutz F4L-1011
Capacity: 11,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 450 hours/ 12 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Change every 20 hours

DIFFERENTIAL FRONT
Capacity: 10,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 150 hours, change every 1350 hours/ 12 months

HUB REDUCTIONS REAR
Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 150 hours, change every 900 hours/ 12 months

TRANSAXLE MANUAL 8/4
Capacity: 6,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 150 hours, change every 1350 hours/ 12 months

HOLDER A SERIES A 550, A 550 S (1990-2001)



TRANSAXLE MANUAL WITH CREEPER GROUP 8/4

Capacity: 7,55 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 150 hours, change every 1350 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 18 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	Perlus AF 68	

Check every 150 hours, change every 1350 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 150 hours, change every 1350 hours/ 12 months

USE		CLIMATE
First change only		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	Perlus AF 68	

Change every 450 hours

USE		CLIMATE
First change only		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Change every 450 hours

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 150 hours, change every 24 months

HOLDER A SERIES A 550, A 550 S (1990-2001)**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 20 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.