

HÜRLIMANN H-6000 H-6170 (1985-1993)**ENGINE**

Capacity: 16,2 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Multifleet SCD 40***Check every 10 hours, change every 150 hours***USE**

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Multifleet SCD 30***Check every 10 hours, change every 150 hours***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Multifleet SHPD 15W-40***Check every 10 hours, change every 150 hours***USE**

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1**Multifleet SCD 20W-20***Check every 10 hours, change every 150 hours***DIFFERENTIAL FRONT (4x4)****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT***Check every 150 hours, change every 1200 hours***HUB REDUCTIONS FRONT (4x4)****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT***Check every 150 hours, change every 1200 hours*

HÜRLIMANN H-6000 H-6170 (1985-1993)**TRANSMISSION MANUAL**

Capacity: 101 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 150 hours, change every 2400 hours***HYDRAULIC SYSTEM**

Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 150 hours, change every 2400 hours***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

PRODUCT RECOMMENDATION 2

ATF-A**POWER STEERING**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

PRODUCT RECOMMENDATION 2

ATF-A*Check every 150 hours, change every 1200 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50 hours*

HÜRLIMANN H-6000 H-6170 (1985-1993)**GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 1200 hours

COOLING SYSTEM

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2400 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.