

HÜRLIMANN JOKER COM3 JOKER 70 - >H10S673WT1E1001 (2010 AND AFTER)



ENGINE Perkins 1000.3-WT3E
Capacity: 7,7 liter, Filter capacity: 1 liter

| USE | | CLIMATE |
|------------------------------|-------------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT

Capacity: 6 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 300 hours, change every 1200 hours/ 24 months

HUB REDUCTIONS FRONT

Capacity: 1,5 liter (each hub)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 300 hours, change every 1200 hours/ 24 months

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 35 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 50 hours, change every 1200 hours/ 24 months

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |

Check every 50 hours

HÜRLIMANN JOKER COM3 JOKER 70 - >H10S673WT1E1001 (2010 AND AFTER)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 50 hours

COOLING SYSTEM

Capacity: 11 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 12 EVO | | |

Check every 10 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.