

HÜRLIMANN SX SX 2000 (2000 AND AFTER)

ENGINE Perkins 1000.6-WT1
Capacity: 15 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 13 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 50 hours, change every 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 2,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 50 hours, change every 12 months

POWER TAKE OFF FRONT
Capacity: 2,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 300 hours, change every 12 months

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 60/60
Capacity: 113 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 300 hours, change every 12 months

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| <i>Check every 50 hours</i> | | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|-----------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| <i>Check every 50 hours</i> | | |

COOLING SYSTEM

Capacity: 16 liter

| USE | | CLIMATE |
|--|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| <i>Check every 10 hours, change every 1200 hours</i> | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.