HÜRLIMANN XA XA 657 (DT) (2000-2004)



PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

ENGINE Perkins 1000.4-A Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30
Check every 50 hours, change every	300 hours	
USE		CLIMATE
First change only		Moderate

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

Change every 50 hours

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

DIFFERENTIAL FRONT/TRANSFERBO Capacity: 6 liter	Κ.	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
	-	·

Check every 50 hours, change every 12 months

HUB REDUCTIONS FRONT Capacity: 1,5 liter		
USE	CLIMA	ATE
Normal	Mod	derate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 1.	onths	

POWER TAKE OFF FRONT
Capacity: 2,5 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Agrifluid HT

CLIMATE

Moderate

Check every 300 hours, change every 12 months

HÜRLIMANN XA XA 657 (DT) (2000-2004)



TRANSAXLE/HYDRAULIC SYSTEM/PO Capacity: 41 liter	WER STEERING	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 300 hours, change every 12	months	

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 50 hours	·	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours		1

COOLING SYSTEM Capacity: 12 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change ever	v 1200 hours	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.