

**HÜRLIMANN XF-H XF-H90 (2004-2009)**

**ENGINE** Perkins 1000.4-WT  
Capacity: 12 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 300 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>

*Change every 50 hours*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Kroontrak MTH 10W-30</b>		

*Check every 10 hours, change every 1200 hours/ 12 months*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Kroontrak MTH 10W-30</b>		

*Check every 10 hours, change every 1200 hours/ 12 months*

**POWER TAKE OFF FRONT**  
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

*Check every 10 hours, change every 1200 hours/ 12 months*

**HÜRLIMANN XF-H XF-H90 (2004-2009)****TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING**

Capacity: 41 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

*Check every 10 hours, change every 1200 hours/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Change every 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours***COOLING SYSTEM**

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Check every 10 hours, change every 1200 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.