## HÜRLIMANN XF XF 481 (1997-2003)



ENGINE Perkins H-1000.4 W Capacity: 9,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 150 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 40
Change every 150 hours		

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change ever	1200 hours	

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,5 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 150 hours, change every 1200 hours

TRANSAXLE/HYDRAULIC SYSTEM 16/Capacity: 33 liter	16	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change every 1200 hours		

## HÜRLIMANN XF XF 481 (1997-2003)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 24 months		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Chook overy 50 hours		

Check every 50 hours

COOLING SYSTEM Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 24 months	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.