

HÜRLIMANN XT XT 910.6 4WD (1997-2004)

ENGINE Perkins 1000.6-W1
Capacity: 15 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|------------------------------|-------------------------------|-----------------------------|
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 |

Check every 50 hours, change every 300 hours/ 12 months

| USE | CLIMATE |
|-------------------|----------|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|------------------------------|-------------------------------|-----------------------------|
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 |

Change every 50 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 10,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT | | |

Check every 300 hours, change every 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 2,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT | | |

Check every 300 hours, change every 12 months

POWER TAKE OFF FRONT
Capacity: 2,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT | | |

Check every 300 hours, change every 12 months

HÜRLIMANN XT XT 910.6 4WD (1997-2004)**TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 60/60**

Capacity: 71 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 300 hours, change every 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 300 hours***GREASE POINTS/NIPPLES**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50 hours***COOLING SYSTEM**

Capacity: 17 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 1200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.