

INTERNATIONAL HARVESTER 43 / 45 743 XL (1981-1985)



ENGINE IH D-239
Capacity: 9 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|------------------------------|--|
| Multifleet SCD 30 | Multifleet SCD 20W-20 | |

Check every 10 hours, change every 200 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-------------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Multifleet SHPD 10W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 200 hours

DIFFERENTIAL FRONT
Capacity: 5,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|------------------------------------|
| Gearlube GL-4 80W-90 | Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 |

Check every 200 hours, change every 800 hours

HUB REDUCTIONS FRONT
Capacity: 0,75 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|------------------------------------|
| Gearlube GL-4 80W-90 | Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 |

Check every 200 hours, change every 800 hours

TRANSAXLE MANUAL 8/4
Capacity: 42 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 200 hours, change every 1600 hours

INTERNATIONAL HARVESTER 43 / 45 743 XL (1981-1985)



HYDRAULIC SYSTEM

Capacity: 18 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |

Check every 50 hours, change every 800 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |

Check every 50 hours, change every 1000 hours

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 1600 hours

COOLING SYSTEM

Capacity: 19,5 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 50 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.