

# JACOBSEN RIDE-ON GREEN AND FAIRWAY MOWERS LF3800 4X4 TIER II 67867/67948



**ENGINE** Kubota V1505-E  
Capacity: 5,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SHPD 10W-40</b> |

*Check every 8 hours, change every 100 hours*

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SHPD 10W-40</b> |

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 37,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|--------------------------|--------------------------|
| <b>Kroontrak MTH 10W-30</b> |                          |                          |

*Check every 50 hours, change every 500 hours/ 12 months*

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Change every 50 hours*

## COOLING SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|--------------------------|--------------------------|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |                          |

*Check every 8 hours, change every 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.