## JOHN DEERE 5E SERIES 5055E (NORTH AMERICA) (2010-2017)



<b>ENGINE</b> John Deere 3029 H Capacity: 8,5 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40
Check every 10 hours, change every 37	5 hours	
USE		CLIMATE
Normal		Moderate

Normal

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

Agrisynth LSP Ultra 10W-40

Moderate

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

Agrisynth LSP 10W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 4,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 600 hours

SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

Check every 50 hours, change every 600 hours

HUB REDUCTIONS FRONT Capacity: 0,8 liter (each hub)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
	<del></del>	-

Check every 50 hours, change every 600 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90
Check every 50 hours, change eve	ery 600 hours	1

## JOHN DEERE 5E SERIES 5055E (NORTH AMERICA) (2010-2017)



Normal CLIMATE  Moderate	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	PRODUCT RECOMMENDATION 1  Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2  Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3  Kroontrak MTH 10W-30
	TRANSAXLE/HYDRAULIC SYSTEM Capacity: 38-39 liter, Capacity: 43,5 liter (F	PowrReverser)	

Check every 50 hours, change every 1200 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Change every 50 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

COOLING SYSTEM Capacity: 9,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Charle avant 10 hours shangs avan		

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.