## JOHN DEERE 6020 SERIES 6220 (-> NR. 398790) (2002-2003)



ENGINE John Deere 4045 TL071 Capacity: 16 liter				
USE		CLIMATE		
Extended		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40		
Check every 10 hours, change every 500 hours/ 12 months				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40		

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 6 liter (APL/AS 2025 + TLS without brakes), Capacity: 5 liter (APL/AS 2025 without TLS), Capacity: 3,6 liter (APL/AS 2035 without TLS)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30		
01 1 0501	15001 /04 //			

Check every 250 hours, change every 1500 hours/24 months

HUB REDUCTIONS FRONT Capacity: 1 liter (APL/AS 2035 + TLS + brakes), Capacity: 0,8 liter (APL/AS 2035 without TLS)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30		
Check every 250 hours, change every 750 hours				

POWER TAKE OFF FRONT
Capacity: 3,5 liter

USE
Normal

PRODUCT RECOMMENDATION 1
Agrifluid Synth XHP Ultra

CLIMATE
Moderate

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30

Check every 250 hours, change every 1500 hours/ 24 months

## JOHN DEERE 6020 SERIES 6220 (-> NR. 398790) (2002-2003)



TRANSAXLE/HYDRAULIC SYSTEM Capacity: 1 liter (+ crawler gear), Capacity	v: 3 liter (+ TLS axle), Capacity: 60 liter (Aut	axle), Capacity: 60 liter (AutoPowr), Capacity: 50 liter (AutoQuad II)  CLIMATE  Moderate
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 250 hours, change every 100	00 hours	

**GREASE POINTS/NIPPLES** USE CLIMATE Mediterranean Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 **Labora Grease** Q5 MP Calcep Grease EP 2 **MP Lithep Grease EP 2** Check every 50 hours USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 **Gear Grease EP 1** Check every 50 hours USE CLIMATE Normal Cold PRODUCT RECOMMENDATION 1 Gear Grease EP 0

COOLING SYSTEM Capacity: 13,5 liter (+ cabin), Capacity: 24 liter (+ intercooler), Capacity: 11 liter (Without cabin)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			
011				

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 50 hours