

JOHN DEERE 6030 SERIES (PREMIUM) 6330 (NORTH AMERICA) (2009-2014)



ENGINE John Deere 4045 HL281
Capacity: 16 liter

USE Extended, fuel sulfur level 0-2000 ppm	CLIMATE Moderate
--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	---	--

Check every 10 hours, change every 500 hours

USE Extended, fuel sulfur level 2000-5000 ppm	CLIMATE Moderate
---	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	---	--

Check every 10 hours, change every 300 hours

USE Normal, fuel sulfur level 2000-5000 ppm	CLIMATE Moderate
---	----------------------------

PRODUCT RECOMMENDATION 1 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
---	--	--

Check every 10 hours, change every 200 hours

USE Normal, fuel sulfur level 0-2000 ppm	CLIMATE Moderate
--	----------------------------

PRODUCT RECOMMENDATION 1 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
---	--	--

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT
Capacity: 6,5 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30
---	---	--

Check every 250 hours, change every 1500 hours/ 24 months

HUB REDUCTIONS FRONT
Capacity: 0,6 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30
---	---	--

Check every 250 hours, change every 750 hours

JOHN DEERE 6030 SERIES (PREMIUM) 6330 (NORTH AMERICA) (2009-2014)



POWER TAKE OFF FRONT

Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 250 hours, change every 1500 hours/ 24 months

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 49-52 liter, Capacity: 1 liter (+ crawler gear), Capacity: 3 liter (+ front wheel drive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 250 hours, change every 1500 hours/ 24 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Change every 50 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

Change every 50 hours

JOHN DEERE 6030 SERIES (PREMIUM) 6330 (NORTH AMERICA) (2009-2014)



COOLING SYSTEM

Capacity: 26,5 liter, Capacity: 29 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.