

# JOHN DEERE 8R SERIES 8360R (NORTH AMERICA) 053101 -> 90000 (2013-2018)



**ENGINE** John Deere PowerTech PSX Stage IIb  
Capacity: 25 liter (1300 MFWD), Capacity: 28 liter (1500 MFWD), Capacity: 27,5 liter (with ILS)

<b>USE</b> Biodiesel B20		<b>CLIMATE</b> Moderate
-----------------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrisynth LSP Ultra FE 5W-30</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrisynth LSP Ultra 10W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agrisynth LSP 10W-40</b>
--	--	--

*Check every 10 hours, change every 125 hours/ 12 months*

<b>USE</b> Normal, fuel sulfur level < 15 ppm		<b>CLIMATE</b> Moderate
--	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrisynth LSP Ultra FE 5W-30</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrisynth LSP Ultra 10W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agrisynth LSP 10W-40</b>
--	--	--

*Check every 10 hours, change every 250 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 13,6 liter (1300 MFWD), Capacity: 18,7 liter (1500 MFWD)

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrifluid Synth XHP Ultra</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrifluid HT-Plus</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Kroontrak MTH 10W-30</b>
---	---	--

*Check every 250 hours, change every 1500 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 3,8 liter (with ILS)

<b>USE</b> Normal		<b>CLIMATE</b> Mediterranean
----------------------	--	---------------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Gearlube GL-5 85W-140</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Unigear LS GL-3/GL-5 85W-140</b>	
---	--	--

*Check every 250 hours, change every 1500 hours*

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>SP Gear 1011</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Syngear TDL 75W-90</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Gearlube HS GL-5 75W-90</b>
--	--	---

*Check every 250 hours, change every 1500 hours*

# JOHN DEERE 8R SERIES 8360R (NORTH AMERICA) 053101 -> 90000 (2013-2018)



## TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 165 liter, Capacity: 175 liter (with ILS)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 1500 hours*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Grease EP 1</b>		

*Change every 50 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Grease EP 0</b>		

*Change every 50 hours*

## COOLING SYSTEM

Capacity: 41 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 10 hours, change every 2000 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.