## JOHN DEERE 8RT SERIES 8360RT (NORTH AMERICA) 905301 -> 907100 (2013-2018)



ENGINE John Deere PowerTech PSX Stage IIIb Capacity: 25 liter				
	CLIMATE			
Biodiesel B20				
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40			
hours/ 12 months				
	CLIMATE			
Normal, fuel sulfur level < 15 ppm				
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40			
	PRODUCT RECOMMENDATION 2 Agrisynth LSP Ultra 10W-40 hours/ 12 months  PRODUCT RECOMMENDATION 2			

TRANSAXLE/HYDRAULIC SYSTEM Capacity: 258 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30	

Check every 10 hours, change every 1500 hours

Check every 10 hours, change every 250 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Change every 50 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		
Change every 50 hours		

## JOHN DEERE 8RT SERIES 8360RT (NORTH AMERICA) 905301 -> 907100 (2013-2018)



COOLING SYSTEM Capacity: 41 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	rv 2000 hours/24 months	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.