

JOHN DEERE 9R(T) SERIES 9510R TIER 4I/STAGE IIIB (2012-2014)



ENGINE John Deere PowerTech PSX 6135
Capacity: 48 liter

USE Normal, fuel sulfur level < 15 ppm	CLIMATE Moderate
--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra FE 5W-30	PRODUCT RECOMMENDATION 2 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40
--	--	--

Check every 10 hours, change every 250 hours

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 3,8 liter (+ hitch), Capacity: 217,7-229,1 liter (Powershift Transmission, DR axles)

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30
---	---	--

Check every 10 hours, change every 1500 hours

GREASE POINTS/NIPPLES

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2
---	--	---

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gear Grease EP 1		
--	--	--

USE Normal	CLIMATE Cold
----------------------	------------------------

PRODUCT RECOMMENDATION 1 Gear Grease EP 0		
--	--	--

COOLING SYSTEM

Capacity: 55 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Coolant SP 12 EVO		
---	--	--

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

JOHN DEERE 9R(T) SERIES 9510R TIER 4I/STAGE IIIB (2012-2014)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.