PRODUCT RECOMMENDATION

# JOHN DEERE GATOR UTILITY VEHICLES PROGATOR 2020 PIN (020001-) (2001-2005)

## ENGINE Yanmar 3TG72
Capacity: 2,1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Asyntho 5W-30** | **Multifleet SHPD 10W-40** | |

*Check every 5 hours, change every 100 hours*

| USE | CLIMATE |
|---|---|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Asyntho 5W-30** | **Multifleet SHPD 10W-40** | |

*Change every 50 hours*

## DIFFERENTIAL FRONT
Capacity: 3,3 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |

*Check every 100 hours, change every 450 hours*

## TRANSAXLE MANUAL
Capacity: 10,6 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |

*Check every 5 hours, change every 450 hours*

## AUXILIARY HYDRAULIC SYSTEM
Capacity: 13,2 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid Synth XHP Ultra** | **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** |

*Check every 5 hours, change every 450 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# JOHN DEERE GATOR UTILITY VEHICLES PROGATOR 2020 PIN (020001-) (2001-2005)

## HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Drauliquid DOT 3** | | |
| *Check every 50 hours* | | |

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |
| *Check every 50 hours* | | |

## COOLING SYSTEM
Capacity: 3,8 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Coolant -38 Organic NF** | **Coolant -26** | |
| *Check every 5 hours, change every 2000 hours/ 24 months* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367