

JOHN DEERE 4000 SERIES 4600 (2WD/4WD) PIN (160001-)(2000-2002)



ENGINE Yanmar 4TNE84
Capacity: 4,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Check every 10 hours, change every 200 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL FRONT

Capacity: 7,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

Check every 50 hours, change every 500 hours

TRANSAXLE HYDROSTATIC/HYDRAULIC SYSTEM

Capacity: 33,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

Check every 10 hours, change every 200 hours

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 25,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

Check every 10 hours, change every 200 hours

JOHN DEERE 4000 SERIES 4600 (2WD/4WD) PIN (160001-)(2000-2002)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 25 hours

COOLING SYSTEM

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.