KUBOTA B SERIES B2400, B2400 HST/BISPEED (1993 AND AFTER)



| ENGINE Kubota D1105-D10 Capacity: 3 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | HDX 30 | |
| Change every 200 hours | · | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 20W-20 | HDX 20W-20 | |
| Change every 200 hours | | · |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Multifleet SHPD 10W-40 | Multifleet SCD 10W |
| Change every 200 hours | 1 | ' |

| DIFFERENTIAL FRONT (4x4) Capacity: 3,7 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Check every 50 hours, change every | hours |

| DIFFERENTIAL FRONT BI-SPEED TRANSMISSION Capacity: 4,5 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Check every 50 hours, change every 300 hours | | |

KUBOTA B SERIES B2400, B2400 HST/BISPEED (1993 AND AFTER)



| TRANSAXLE HYDROSTATIC/HYDRAUL Capacity: 12 liter | IC SYSTEM | |
|--|-----------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Change every 300 hours | | |

| TRANSAXLE/HYDRAULIC SYSTEM Capacity: 11 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Change every 300 hours | , |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| Check every 50 hours | 1 | 1 |

| COOLING SYSTEM Capacity: 3,4 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Change every 24 months | , | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.