

# KUBOTA L SERIES L235 KUBOTA D1102A

## (1980-1988)



**ENGINE** Kubota D1102A  
Capacity: 6,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Multifleet SCD 30</b> | <b>HDX 30</b>            |  |

*Check every 10 hours, change every 75 hours*

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 |  |
|------------------------------|--------------------------|--|
| <b>Multifleet SCD 20W-20</b> | <b>HDX 20W-20</b>        |  |

*Check every 10 hours, change every 75 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |  |
|-----------------------------|-------------------------------|--|
| <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SHPD 10W-40</b> |  |

*Check every 10 hours, change every 75 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |  |
|---------------------------|--------------------------|--|
| <b>Multifleet SCD 10W</b> | <b>HDX 10W</b>           |  |

*Check every 10 hours, change every 75 hours*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 1,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |

*Change every 300 hours*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 0,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |

*Change every 300 hours*

# KUBOTA L SERIES L235 KUBOTA D1102A

(1980-1988)



## TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 24 liter

| USE                              |                             | CLIMATE                  |
|----------------------------------|-----------------------------|--------------------------|
| Normal                           |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

Check every 10 hours, change every 300 hours

## POWER STEERING

Capacity: 1,5 liter

| USE                          |                           | CLIMATE                  |
|------------------------------|---------------------------|--------------------------|
| Normal                       |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Multifleet SCD 20W-20</b> | <b>Multifleet SCD 10W</b> | <b>HDX 20W-20</b>        |

Check every 75 hours, change every 400 hours

## GREASE POINTS/NIPPLES CLUTCH RELEASE BEARING

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Check every 300 hours

## GREASE POINTS/NIPPLES OTHERS

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Check every 50 hours

## GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Check every 300 hours

# KUBOTA L SERIES L235 KUBOTA D1102A

## (1980-1988)



### COOLING SYSTEM

Capacity: 6,6 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26***Check every 10 hours, change every 12 months*

### STEERING BOX

Capacity: 0,3 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015**

## PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W***Check every 150 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.