## KUBOTA M SERIES M130X WITH EGR (2010 AND AFTER)



apacity: 14,6 liter		
SE		CLIMATE
itial service		Tropical
CODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
gridiesel CRD+ 15W-40	Multifleet SCD 30	
hange every 50 hours		
SE .		CLIMATE
itial service		Mediterranean
coduct recommendation 1 ultifleet SCD 20W-20		
hange every 50 hours		
SE		CLIMATE
itial service		Moderate
CODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
grisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40
hange every 50 hours		·
BE		CLIMATE
itial service		Arctic
RODUCT RECOMMENDATION 1		
ultifleet SCD 10W		
hange every 50 hours		
SE .		CLIMATE
ormal, fuel sulfur level < 500 ppm		Tropical
	PRODUCT RECOMMENDATION 2	
gridiesel CRD+ 15W-40	Multifleet SCD 30	
hange every 400 hours		
SE		CLIMATE
ormal, fuel sulfur level < 500 ppm		Mediterranean
ODUCT RECOMMENDATION 1		
ultifleet SCD 20W-20		
hange every 400 hours		
SE		CLIMATE
ormal, fuel sulfur level < 500 ppm		Moderate
		PRODUCT RECOMMENDATION 3  Kroontrak CVT 10W-40
	PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40	

## KUBOTA M SERIES M130X WITH EGR (2010 AND AFTER)



USE	CLIMATE
Normal, fuel sulfur level < 500 ppm	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 400 hours	
DIFFERENTIAL FRONT Capacity: 12 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 600 hours	
GEAR CASE FRONT Capacity: 4,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 600 hours	
TRANSMISSION Capacity: 60 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 600 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	 
Agrifluid HT	
Change every 50 hours	

PRODUCT RECOMMENDATION

## KUBOTA M SERIES M130X WITH EGR (2010 AND AFTER)



Agrifluid HT	
PRODUCT RECOMMENDATION 1	
Normal	Moderate
USE	CLIMATE
HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter	

COOLING SYSTEM Capacity: 15 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 24 months	•		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.