## **KUBOTA M SERIES M6040N KUBOTA** V3307-DI-TE3 (2007-2013)



ENGINE Kubota V3307-DI-TE3 Capacity: 11 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 300 hours	,	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 300 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Dieselfleet LSP Ultra 10W-30
Change every 300 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 300 hours		
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 50 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Dieselfleet LSP Ultra 10W-30
Change every 50 hours		

## KUBOTA M SERIES M6040N KUBOTA V3307-DI-TE3 (2007-2013)



USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

DIFFERENTIAL FRONT Capacity: 5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Change every 600 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 50 hours	

HUB REDUCTIONS FRONT Capacity: 3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 600 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Change every 50 hours

## KUBOTA M SERIES M6040N KUBOTA V3307-DI-TE3 (2007-2013)



TRANSMISSION 12/12 Capacity: 56 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 600 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 50 hours	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM Capacity: 9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 24 months	,		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.