KUBOTA FRONT MOUNTED TRACTOR MOWERS F3560 (1999 AND AFTER)



ENGINE Capacity: 2,7 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 100 l	hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every 100 l	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Check every 10 hours, change every 100 l	hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 100 l	hours	
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 50 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Change every 50 hours		

KUBOTA FRONT MOUNTED TRACTOR MOWERS F3560 (1999 AND AFTER)



USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

DIFFERENTIAL REAR Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
<u> </u>	

Check every 10 hours, change every 200 hours

HUB REDUCTIONS REAR Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Charle avery 10 hours shange avery 200 h	2011/20	

Check every 10 hours, change every 200 hours

TRANSMISSION Capacity: 13,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 10 hours, change every 200 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

KUBOTA FRONT MOUNTED TRACTOR MOWERS F3560 (1999 AND AFTER)



COOLING SYSTEM Capacity: 4,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.