## LAMBORGHINI CHAMPION CHAMPION 135 (1998-2003)



ENGINE Perkins 1000.6-WT Capacity: 15,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 10 hours, change every 300 hours/ 12 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Oh		

Change every 50 hours

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Charle even (450 hours, charge even (4000 hours) (40 months		

Check every 150 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 150 hours, change every 1200 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change every 1200 hours/ 12 months		

## LAMBORGHINI CHAMPION CHAMPION 135 (1998-2003)



TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING Capacity: 108 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT		

Check every 150 hours, change every 1200 hours/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check event 200 hours, change event 24 months		

Check every 300 hours, change every 24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

Check every 50 hours

COOLING SYSTEM Capacity: 16 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

AIRCONDITIONING COMPRESSOR Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -33 MPG	
Change every 12 months	

## LAMBORGHINI CHAMPION CHAMPION 135 (1998-2003)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.