LAMBORGHINI CHAMPION CHAMPION 180



(2000-2003)

ENGINE Perkins 1000.6-WTI Capacity: 15,5 liter	
use Normal	CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40	

Check every 10 hours, change every 300 hours/12 months

DIFFERENTIAL FRONT (4x4) Capacity: 13 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 150 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 150 hours, change every 1200 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Charles your 450 hours shange over 4200 hours/42 months		

Check every 150 hours, change every 1200 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING Capacity: 108 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change every 120	0 hours/ 12 months	

LAMBORGHINI CHAMPION CHAMPION 180

(2000-2003)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8 liter	
use Normal	CLIMATE Moderate
PRODUCT RECOMMENDATION 1 ATF Dexron II-D	

Check every 300 hours, change every 24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	
Check every 50 hours		,

COOLING SYSTEM
Capacity: 16 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Capacity: 16 liter

CLIMATE
Moderate

Moderate

PRODUCT RECOMMENDATION 2

Coolant -26

Check every 10 hours, change every 24 months

AIRCONDITIONING COMPRESSOR Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -33 MPG	
Change every 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.