LAMBORGHINI R R 1706, -DT (1985-1990)



ENGINE 1106/17T Capacity: 16,2 liter			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 40	HDX 40		
Check every 10 hours, change every 150 l	hours		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
HDX 30			
Check every 10 hours, change every 150 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SHPD 15W-40	HDX 20W-20		
Check every 10 hours, change every 150 hours			

DIFFERENTIAL FRONT (4x4) Capacity: 13 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT			
011	10001		

Check every 150 hours, change every 1200 hours

HUB REDUCTIONS FRONT (4x4) Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 125 hours, change every 1000 hours		

LAMBORGHINI R R 1706, -DT (1985-1990)



TRANSAXLE/HYDRAULIC SYSTEM 16/12 Capacity: 97 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change every 2400 hours		

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	Perlus Biosynth 46	Perlus H 46

POWER STEERING Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	Perlus Biosynth 46	Perlus H 46
Check every 125 hours, change ev	rery 1000 hours	'

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	
	<u> </u>	

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2		
Change every 1200 hours		,	

LAMBORGHINI R R 1706, -DT (1985-1990)



COOLING SYSTEM Capacity: 18 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 2400 hours/ 24 month	is	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.