LAMBORGHINI R3 T-TB R3.T 75 (2008-2009)



PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

| ENGINE Perkins 1000.4-W Capacity: 12 liter, Filter capacity: 1 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 |
| Check every 10 hours, change every 300 hours/ 12 months | | |
| USE | | CLIMATE |
| Initial service | | Moderate |

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

Change every 50 hours

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

| DIFFERENTIAL FRONT (4x4) Capacity: 6 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Kroontrak MTH 10W-30 | |

Check every 10 hours, change every 1200 hours/ 12 months

| HUB REDUCTIONS FRONT (4x4) Capacity: 1,5 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Kroontrak MTH 10W-30 | |
| | |

Check every 10 hours, change every 1200 hours/ 12 months

| POWER TAKE OFF FRONT Capacity: 2,5 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 10 hours, change every 1200 hours/ 12 months | | |

LAMBORGHINI R3 T-TB R3.T 75 (2008-2009)



| TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING Capacity: 52 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 10 hours, change every 1200 hours/12 months | | |

Check every 10 hours, change every 1200 hours/ 12 months

| HYDRAULIC BRAKE/CLUTCH SYSTEM | | |
|-------------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| Change every 24 months | | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2 | |
| Change every 50 hours | ' | ' |

| COOLING SYSTEM Capacity: 11 liter | | |
|-----------------------------------|---------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |
| Check every 10 hours, change eve | ury 1200 hours/ 12 months | |

Check every 10 hours, change every 1200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.