## LAMBORGHINI R3 T-TB R3.T 95 (2008-2009)



<b>ENGINE</b> Perkins 1000.4-WT Euro 2 Capacity: 12 liter, Filter capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30
Check every 10 hours, change every 300 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Agridiesel MSP 15W-40
 Agridiesel CRD+ 15W-40
 Kroontrak MTH 10W-30

Change every 50 hours

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 6 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Charles ware 10 hours a charge avery 1200 hours (12 months		

Check every 10 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 1,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Check every 10 hours, change every 1200 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 10 hours, change every 1200 hours/ 12 months		

## LAMBORGHINI R3 T-TB R3.T 95 (2008-2009)



TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING Capacity: 52 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 10 hours, change every 1200 hours/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change avenu 21 months		

Change every 24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	

Change every 50 hours

COOLING SYSTEM Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change every 1200 hours/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.