

**LAMBORGHINI R3 R3.85 ->5001 (2010-2015)**

**ENGINE** Perkins 1000.4-W  
Capacity: 11 liter, Filter capacity: 1 liter

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrisynth LSP 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agridiesel MSP 15W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agridiesel CRD+ 15W-40</b>
--	---	--

*Check every 10 hours, change every 600 hours*

<b>USE</b> Biodiesel B100		<b>CLIMATE</b> Moderate
------------------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrisynth LSP 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agridiesel MSP 15W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agridiesel CRD+ 15W-40</b>
--	---	--

*Check every 10 hours, change every 300 hours*

**DIFFERENTIAL FRONT**

Capacity: 6 liter

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Kroontrak CVT 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrifluid Synth XHP Ultra</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agrifluid HT-Plus</b>
--	---	---

*Check every 300 hours, change every 1200 hours/ 24 months*

**HUB REDUCTIONS FRONT**

Capacity: 1,5 liter

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Kroontrak CVT 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrifluid Synth XHP Ultra</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agrifluid HT-Plus</b>
--	---	---

*Check every 300 hours, change every 1200 hours/ 24 months*

**TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING**

Capacity: 52 liter

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Kroontrak CVT 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrifluid Synth XHP Ultra</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agrifluid HT-Plus</b>
--	---	---

*Check every 50 hours, change every 1200 hours/ 24 months*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

**COOLING SYSTEM**

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		

*Check every 10 hours, change every 1200 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*