

LAMBORGHINI R6 VRT R6.190 VRT DCR STAGE 3A->10001 (2010-2015)



ENGINE Deutz TCD 2012 L06 4V DCR
Capacity: 15,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|------------------------------|-------------------------------|
| Agrisynth LSP 10W-40 | Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 |

Check every 10 hours, change every 500 hours/ 12 months

| USE | CLIMATE |
|----------------|----------|
| Biodiesel B100 | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|------------------------------|-------------------------------|
| Agrisynth LSP 10W-40 | Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 |

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 5,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 0,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS REAR
Capacity: 5 liter (each hub)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 250 hours, change every 1000 hours/ 12 months

LAMBORGHINI R6 VRT R6.190 VRT DCR STAGE 3A->10001 (2010-2015)



POWER TAKE OFF FRONT

Capacity: 1,8 liter

| USE | | CLIMATE |
|-----------------------------|----------------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agrifluid Synth XHP Ultra | Agrifluid HT-Plus |

Check every 250 hours, change every 500 hours

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 67 liter

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak CVT 10W-40 | | |

Check every 50 hours, change every 1000 hours/ 12 months

AUXILIARY HYDRAULIC SYSTEM

Capacity: 60 liter

| USE | | CLIMATE |
|-----------------------------|----------------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agrifluid Synth XHP Ultra | Agrifluid HT-Plus |

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |

Check every 50 hours

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 50 hours

LAMBORGHINI R6 VRT R6.190 VRT DCR STAGE 3A->10001 (2010-2015)

**COOLING SYSTEM**

Capacity: 21 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 12 EVO***Check every 10 hours, change every 1000 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.