Agrifluid HT

LAMBORGHINI RACING 165 RACING (1992-2001)



ENGINE Perkins 1000.6-WTI Capacity: 15 liter, Filter capacity: 0,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 10 hours, change every 150 hours/ 12 months		

DIFFERENTIAL FRONT (4x4)
Capacity: 13 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1

Check every 150 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 125 hours, change every 1200 hours/ 12 months

POWER TAKE OFF Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check over 450 hours shows ever 4200 hours		

Check every 150 hours, change every 1200 hours

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 27/27 Capacity: 108 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change every 1200 hours/ 12 months		

LAMBORGHINI RACING 165 RACING (1992-2001)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 300 hours change every 24	months	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	
Check every 50 hours		

COOLING SYSTEM Capacity: 16 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -33 MPG		
Chack ayany 10 haurs, change ayany 2/	00 hours/24 months	

Check every 10 hours, change every 2400 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.