LAMBORGHINI RACING 190 RACING II (H.P.) (1992-2001)



| ENGINE Perkins 1000.6-WTIR Capacity: 15 liter, Filter capacity: 0,5 liter | |
|--|-------------------|
| use Normal | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40 | |

Check every 10 hours, change every 150 hours/ 12 months

| DIFFERENTIAL FRONT (4x4) Capacity: 13 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT | |
| | |

Check every 150 hours, change every 1200 hours/ 12 months

| CLIMATE |
|----------|
| Moderate |
| |
| |
| |

Check every 125 hours, change every 1200 hours/ 12 months

| POWER TAKE OFF Capacity: 2,5 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 150 hours, change every 1200 hours | | |

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 27/27
Capacity: 108 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 150 hours, change every 1200 hours/ 12 months

LAMBORGHINI RACING 190 RACING II (H.P.)



(1992-2001)

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8 liter | | |
|---|--------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| Chack avery 200 hours, change avery 24 i | nonths | |

Check every 300 hours, change every 24 months

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2 | |
| Check every 50 hours | | <u> </u> |

| COOLING SYSTEM Capacity: 16 liter | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -33 MPG | |
| | |

Check every 10 hours, change every 2400 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.