PRODUCT RECOMMENDATION

LAMBORGHINI RF COM3 RF.100 - >1001/10001 (2011-2015)

ENGINE Perkins 1000.4-WTI Euro 3
Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	**Agridiesel MSP 15W-40**	**Agridiesel CRD+ 15W-40**

Check every 10 hours, change every 300 hours

USE	CLIMATE
Biodiesel B100	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	**Agridiesel MSP 15W-40**	**Agridiesel CRD+ 15W-40**

Check every 10 hours, change every 150 hours

DIFFERENTIAL FRONT
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus	**Agrifluid HT**

Check every 300 hours, change every 1200 hours/ 24 months

HUB REDUCTIONS FRONT
Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus	**Agrifluid HT**

Check every 300 hours, change every 1200 hours/ 24 months

POWER TAKE OFF FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus	**Agrifluid HT**

Check every 300 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

LAMBORGHINI RF COM3 RF.100 - >1001/10001 (2011-2015)

TRANSMISSION
Capacity: 41 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	**Agrifluid HT**	

Check every 50 hours, change every 1200 hours/ 24 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 50 hours, change every 1200 hours/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 50 hours

COOLING SYSTEM
Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 10 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367