

LANDINI MISTRAL MISTRAL 40/40 HST

EURO 2 (2004-2008)



ENGINE Yanmar 3TNV88 - KLAN
Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT
Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 100 hours, change every 1000 hours/ 12 months

HYDROSTATIC TRANSMISSION HST
Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 100 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
ATF-A		

Change every 500 hours

POWER TAKE OFF FRONT
Capacity: 0,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 50 hours

LANDINI MISTRAL MISTRAL 40/40 HST

EURO 2 (2004-2008)



TRANSMISSION/HYDRAULIC SYSTEM STD

Capacity: 24 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 100 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Change every 500 hours

COOLING SYSTEM

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.